



TECHNICAL SPECIFICATION

RESPINACABLE

Electrical Wire and Cable



Wire 1 x 1 (N)YA

P.V.C - insulated ,non Sheathed,Single-Core Cable with rigid Conductor H05V-U, 300/500 V ACC.ISIRI(607)

Cable Layer Construction		CU , PVC		LV
Applicable Standard(s)		IEC 60227 & ISIRI 607 & DIN VDE 0271 & IEC 60228		
Description			Unit	Specification
CONDUCTOR	CU	Material	****	Plain Annealed Copper
		TYPE	****	Solid (Class 1) RE
		No.of core & Conductor Area	mm ²	1 x 1
		No & Dia of Strand	no * mm	1 x 1.13
		Shape	****	ROUND
INSULATION	PVC	Material	****	Extruded PVC
		Thickness Phase	mm	0.6
		Colour	****	Request
Approx. overall diameter of cable			mm	2.33
Approx. Weight of cable			Kg/ km	13.50
Packing			****	Drum
Rated Voltage U0/U (Um)			V	300 / 500
System Frequency			Hz	50
DC conductor resistant At 20 °C			Ω/ Km	18.1
Cable Voltage test			KV	2.5
Max.Short circuit withstand current temperature			°C	+ 160
Operation temperature			°C	- 30 to +70
Special Proerties			Flame Retardant	IEC 60332-1-2



ISIRI(607)06 6950954946 H05V-K 300/500V 1x0.5 mm2 RF MADE IN IRAN CE

TEL : +98 21 46808941 FAX : +98 21 46808236 WWW.RESPINACABLE.COM